

BERNARD® STYLE GUN CONFIGURATOR

| Amperage | |
|-------------|----------|
| BQ20 | 200 Amps |
| BQ30 | 300 Amps |
| BQ35 | 350 Amps |
| BQ40 | 400 Amps |
| BQ50 | 500 Amps |
| BQ60 | 600 Amps |

| Gun Length | |
|------------|----------------|
| 10 | 10 ft. (3.05m) |
| 12 | 12 ft. (3.66m) |
| 15 | 15 ft. (4.57m) |
| 20 | 20 ft. (6.16m) |
| 25 | 25 ft. (7.63m) |

| Handle and Trigger | | |
|--------------------|----------|------------------|
| 200, 300 Amp | A | Standard Trigger |
| Curved Handle | | |
| 400 Amp | A | Standard Trigger |
| Curved Handle | | |
| 500 Amp | A | Standard Trigger |
| Curved Handle | | |
| 600 Amp | A | Standard Trigger |
| Straight Handle | | |

BQ40 15 A E 4C M C*

| Neck | | | |
|----------|-------------------|-----|---------|
| A | Rotatable, Short | 30° | BQT2-30 |
| B | Rotatable, Short | 45° | BQT2-45 |
| C | Rotatable, Short | 60° | BQT2-60 |
| J | Rotatable, Short | 80° | BQT2-80 |
| D | Rotatable, Medium | 30° | BQT3-30 |
| E | Rotatable, Medium | 45° | BQT3-45 |
| F | Rotatable, Medium | 60° | BQT3-60 |
| K | Rotatable, Medium | 80° | BQT3-80 |
| G | Rotatable, Long | 30° | BQT5-30 |
| H | Rotatable, Long | 45° | BQT5-45 |
| I | Rotatable, Long | 60° | BQT5-60 |
| N | Fixed, Short | 30° | BQT2-30 |
| O | Fixed, Short | 45° | BQT2-45 |
| P | Fixed, Short | 60° | BQT2-60 |
| W | Fixed, Short | 80° | BQT2-80 |
| Q | Fixed, Medium | 30° | BQT3-30 |
| R | Fixed, Medium | 45° | BQT3-45 |
| S | Fixed, Medium | 60° | BQT3-60 |
| X | Fixed, Medium | 80° | BQT3-80 |
| T | Fixed, Long | 30° | BQT5-30 |
| U | Fixed, Long | 45° | BQT5-45 |
| V | Fixed, Long | 60° | BQT5-60 |

| Contact Tip | | |
|------------------------|----------------|-----------|
| 7400 Series | | |
| 7A | 0.023" (0.6mm) | B7497 |
| 7B | 0.030" (0.8mm) | B7488 |
| 7C | 0.035" (0.9mm) | B7489 |
| 7D | 0.039" (1.0mm) | B7496 |
| 7E | 0.045" (1.2mm) | B7490 |
| 7H | 0.052" (1.4mm) | B7498 |
| 7I | 1/16" (1.6mm) | B7491 |
| 7K | 5/64" (2.0mm) | B7492 |
| 7L | 3/32" (2.4mm) | B7493 |
| 7M | 7/64" (2.8mm) | B7494 |
| 1500 Series | | |
| 1A | 0.023" (0.6mm) | B1597 |
| 1B | 0.030" (0.8mm) | B1588 |
| 1C | 0.035" (0.9mm) | B1589 |
| 1D | 0.039" (1.0mm) | B1596 |
| 1E | 0.045" (1.2mm) | B1590 |
| 1H | 0.052" (1.4mm) | B1598 |
| 1I | 1/16" (1.6mm) | B1591 |
| 1K | 5/64" (2.0mm) | B1592 |
| 1L | 3/32" (2.4mm) | B1593 |
| 1M | 7/64" (2.8mm) | B1594 |
| CMI Taper-LOCK™ | | |
| 4B | 0.030" (0.8mm) | 155-1-030 |
| 4C | 0.035" (0.9mm) | 155-1-035 |
| 4D | 0.040" (1.0mm) | 155-1-040 |
| 4E | 0.045" (1.2mm) | 155-1-045 |
| 4F | 3/64" (1.3mm) | 155-1-364 |
| 4H | 0.052" (1.4mm) | 155-1-052 |
| 4I | 1/16" (1.6mm) | 155-1-062 |
| 4K | 5/64" (2.0mm) | 155-1-564 |
| 4L | 3/32" (2.4mm) | 155-1-332 |

| Power Pin | |
|-----------|--------------------------|
| B | Bernard™ |
| E | Euro |
| H | Hobart® |
| L | Lincoln® LN |
| S | Lincoln® LF/Power Feed |
| R | Lincoln® Power MIG |
| M | Miller® |
| O | OXO® |
| P | Panasonic® |
| T | Tweco® 4 (Standard Lead) |
| W | Tweco® 5 (Standard Lead) |

*Liner Style

Add **C** to the end of the part# for Universal Conventional Liner
Leave blank for old style Liner