

Bernard - T-Series Configurator

Amperage

RQ30	300 Amps
RQ40	400 Amps
RQ50	500 Amps
RQ60	600 Amps

Gun Length

10	10 ft. (3.05m)
12	12 ft. (3.66m)
15	15 ft. (4.57m)
20	20 ft. (6.10m)
25	25 ft. (7.63m)

Handle and Trigger

300 Amp	M	Std. Trigger, T-Series Straight Handle
400 Amp	M	Std. Trigger, T-Series Straight Handle
500 Amp	M	Std. Trigger, T-Series Straight Handle
600 Amp	M	Std. Trigger, T-Series Straight Handle

RQ40 15 M S 4E M C*

Neck

A	Rotatable, Short	30°	BQT2-30
B	Rotatable, Short	45°	BQT2-45
C	Rotatable, Short	60°	BQT2-60
J	Rotatable, Short	80°	BQT2-80
D	Rotatable, Medium	30°	BQT3-30
E	Rotatable, Medium	45°	BQT3-45
F	Rotatable, Medium	60°	BQT3-60
K	Rotatable, Medium	80°	BQT3-80
G	Rotatable, Long	30°	BQT5-30
H	Rotatable, Long	45°	BQT5-45
I	Rotatable, Long	60°	BQT5-60
O	Fixed, Short	45°	R305-45
P	Fixed, Short	60°	R305-60
R	Fixed, Medium	45°	R405-45
S	Fixed, Medium	60°	R405-60
U	Fixed, Long	45°	R505-45
V	Fixed, Long	60°	R505-60

Contact Tip

CMI Taper-LOCK™

4B	.030"	(0.8mm)	155-1-030
4C	.035"	(0.9mm)	155-1-035
4D	.040"	(1.0mm)	155-1-040
4E	.045"	(1.2mm)	155-1-045
4R	3/64"	(1.3mm)	155-1-364
4H	.052"	(1.4mm)	155-1-052
4I	1/16"	(1.6mm)	155-1-062
4K	5/64"	(2.0mm)	155-1-564
4L	3/32"	(2.4mm)	155-1-332

Contact Tip

Comparable to Tregaskiss® Tough Lock™

3B	.030"	(0.8mm)	R403-20-30
3C	.035"	(0.9mm)	R403-20-35
3D	.040"	(1.0mm)	R403-20-1.0
3E	.045"	(1.2mm)	R403-20-45
3R	3/64"	(1.3mm)	R403-20-364
3H	.052"	(1.4mm)	R403-20-52
3I	1/16"	(1.6mm)	R403-20-116
3K	5/64"	(2.0mm)	R403-20-564
3L	3/32"	(2.4mm)	R403-20-332

Contact Tip

Comparable to Bernard® Centerfire™

8B	.030"	(0.8mm)	T-030
8C	.035"	(0.9mm)	T-035
8D	.039"	(1.0mm)	T-039
8E	.045"	(1.2mm)	T-045
8R	3/64"	(1.3mm)	T-047AL
8H	.052"	(1.4mm)	T-052
8I	1/16"	(1.6mm)	T-062
8K	5/64"	(2.0mm)	T-078
8L	3/32"	(2.4mm)	T-094

Power Pin

B	Bernard®
E	Euro
L	Lincoln® LN
S	Lincoln® LF/Power Feed (Tweco® 4 w/ Lincoln Lead)
R	Lincoln® Power MIG (Tweco® 4 w/ Miller Lead)
M	Miller®
T	Tweco® 4 (Standard Lead)
W	Tweco® 5 (Standard Lead)
X	Tweco® 5 (Miller Lead)

***Universal Conventional Liner**